



AUN Fd CLEANER / DEGREASER

Powerful, high-performance, cleaning and degreasing product, leaves no residues, for mechanical components and diving equipment.

Recommended prior to applying perfluoropolyether lubricants in contact with pure oxygen.

Recommended for degreasing scuba tanks following repressurizing.

USERS:

Army, Maintenance workshops, Professionals, etc.

CHARACTERISTICS:

- **Registered INS H1**
- *Colour: Colourless DIN ISO 2049*
- *Base: Solvent Base*
- *Evaporation index: 19 (Ether I)*
- *Wide temperature range: - 30 – + 80 °C*

ADVANTAGES:

- *Rapid, residue-free cleaning of oils, grease, certain resins, waxes and dirt, salt agglomerates.*
- *Evaporates rapidly with no residue*
- *Compatible with most plastics*
- *Fast, effective cleaning*
- *Pleasant fragrance*
- *Cost-effective use*
- *Can be used on hot surfaces up to +80°C.*

METHOD OF USE:

Spray onto the surfaces to be treated Repeat the process on heavily soiled parts. Wait until the product has completely evaporated.

Check compatibility with plastics and varnishes before applying.

Do not use on powered up machinery.

When cleaning breathable air tanks, fill the air tank up to 50/100 bars after applying AUN Fd, then empty it before use and refilling with breathable gas in order to flush out any VOC residues in the tank.

PACKAGING:

- 400 mL aerosol
- 1 L bottle
- 5L/20L can

IDENTIFICATION OF HAZARDS: AEROSOLS

Labelling according to regulation (EC) No. 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Warning statement Hazard



GHS07

Hazard-determining components of labelling:

Naphtha (Petroleum), hydrodesulfurised heavy Naphtha (Petroleum) hydrotreated light



Hazard statements

H222-H229 Highly flammable aerosol. Pressurised container: may burst if heated.

H315 Causes skin irritation. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic organisms, causes long-term adverse effects.

Safety advice

P210 Keep away from heat, hot surfaces, sparks, naked flames and any other source of ignition. Do not smoke. P211 Do not spray near a naked flame or on any other source of ignition.

P251 Do not pierce or burn, even after use.

P302+P352 IN THE EVENT OF CONTACT WITH SKIN: Wash thoroughly with water.

P410+P412 Keep out of direct sunlight. Do not expose to temperatures above 50 °C/122 °F.

P501 Dispose of the container/recipient in accordance with local/regional/national/international regulations.

Additional indications:

EUH066 Repeated exposure may cause skin dryness or cracking.

41.1.0

Buildup of explosive mixtures possible without sufficient ventilation.

IDENTIFICATION OF HAZARDS: BULK

Labelling according to regulation (EC) No. 1272/2008 The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02



GHS08



GHS09

Warning statement Hazard

Hazard statements

H226 Flammable liquid and fumes. H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic organisms, causes long-term adverse effects.

Safety advice: P210 Keep away from heat, hot surfaces, sparks, naked flames and any other source of ignition. Do not smoke.

P241 Use flameproof electrical / ventilation / lighting / equipment

P301+P310 IF SWALLOWED: Call an ANTI-POISON Centre / doctor immediately.

P303+P361+P353 IN THE EVENT OF CONTACT WITH SKIN (or hair): Immediately remove all contaminated clothing. Rinse skin with water / Shower. P405 Store under lock and key. P501 Dispose of the container/recipient in accordance with local/regional/national/international regulations.