



ITN SP: MULTI-PURPOSE LUBRICATING SPRAY / CONTACT O₂

High-performance, PFPE-based lubricant, for use on sensitive surfaces, contact with Oxygen (up to 100% O₂) or at high temperatures.

USERS:

Professional divers, Army and Civil Protection divers, businesses, maintenance workshops, leisure divers, nautical organisations, etc.

TECHNICAL DATA:

- *Colour: transparent colourless*
- *Base: PFPE*
- *Density at 25°C: 1.9 g/cm³ DIN 51757*
- *Base oil viscosity at 40 °C: 80 mm²/s DIN 53015*
- *Flash point: non-flammable °C*
- *Dropping point: none*
- *Maximum peak temperature: +250°C*

ADVANTAGES:

- *Registered NSF H1 (food contact approved)*
- *Compatible with PFPE lubricants*
- *No hazard pictogram required*
- *Very low rate of evaporation, even at very high temperatures*
- *Non-flammable*
- *100% safe on plastics and elastomers*
- *Silicone-free*
- *Efficient, cost-effective and easy to apply*
- *Withstands harsh environments (solvents, acids, etc.)*
- *Rapid drying time at ambient temperature*
- *Excellent protection against rust*

METHOD OF USE:

For the first application, surfaces must be clean and completely free of any residues of oil, grease, finger marks and dirt.

To guarantee optimum lubrication, we recommend cleaning surfaces to be treated with AUN Fd, and then with ITN Clean if necessary.

Apply in thin, even layers on clean surfaces.

Shake well before use (aerosol).

Use-by date: 2 years

PACKAGING:

250ml aerosol can

USE PRECAUTIONS:

Product not considered hazardous within the meaning of current regulations. For further information, please refer to the safety data sheet.